

HP LaserJet Enterprise P3015 Printer (CE525A) - Specifications

Specifications	
Print speed black (normal, A4)	Up to 40 ppm
Print speed footnote	Exact speed varies depending on the system configuration, software application, and document complexity.
Print quality black (best)	Up to 1200 x 1200 dpi
Print technology	Laser
Duty cycle (monthly, A4)	Up to 100,000 pages
Duty cycle note	Duty cycle is defined as the maximum number of pages per month of imaged output. This value provides a comparison of product robustness in relation to other HP LaserJet or HP Color LaserJet devices, and enables appropriate deployment of printers and MFPs to satisfy the demands of connected individuals or groups.
Recommended monthly page volume	1500 to 5000
Standard memory	96 MB
Maximum memory	608 MB
Processor speed	540 MHz
Hard disk capacity	Optional, HP High-Performance Secure EIO Hard Disk (EIO Hard Drive)
Standard printer languages	HP PCL 5e; HP PCL 6; HP postscript level 3 emulation; direct PDF (v 1.4) printing
Paper handling	
Standard paper trays	2
Maximum paper trays	4
Paper handling standard/input	100-sheet multipurpose tray 1; one 500-sheet input tray 2
Paper handling	Optional 500-sheet paper tray (add up to 2)

optional/input	
Paper handling standard/output	250-sheet output bin; 100-sheet rear output bin
Duplex print options	Manual (driver support provided)
Media sizes supported	A4; A5; B5 (JIS); A6
Custom media sizes	Multipurpose tray: 76 x 127 to 216 x 356 mm; tray 2 and optional 500-sheet feeder/tray (3 and 4): 105 x 148 to 216 x 356 mm
Media types supported	Paper (bond, color, letterhead, plain, preprinted, prepunched, recycled, rough); envelopes; labels; cardstock; transparencies; user-defined
Finished output handling	Sheetfed
Connectivity	
Standard connectivity	1 Hi-Speed USB 2.0; 1 external Host USB; 2 internal Accessory ports for HP and partner solutions; 1 EIO slot
Optional connectivity	HP Jetdirect EIO internal print servers; HP Jetdirect external print servers; HP 802.11b/g wireless print servers; HP EIO Parallel Port Adaptor
Dimensions and Weight	
Media weights by paper path	Tray 1: 60 to 199 g/m ² (straight through paper path for special media); tray 2, 3: 60 to 120 g/m ²
Product dimensions (W x D x H)	448 x 412 x 316 mm
Product weight	15.9 kg
Power and operating requirements	
Minimum system requirements	Mac OS X v 10.2.8, 10.3.9, 10.4.3, 10.5; 200 MB available hard disk space; USB (compatible with USB 2.0 specifications) port or IEEE 1284-B compliant parallel port; CD-ROM drive
Compatible operating systems	Windows 2000 (SP4); Windows XP Home; Windows XP Professional; Windows Vista(R); Windows Vista(R) x64; Windows Server 2003; Windows Server 2008; Mac OS X v 10.4 or higher; Novell NetWare; Red Hat Linux 7.x or higher; SuSE Linux 8.x or higher
Power requirements	Input voltage 100 to 127 VAC (+/- 10%), 50/60 Hz (+/- 2

	Hz); 220 to 240 VAC (+/- 10%), 50/60 Hz (+/- 2 Hz)
Recommended operating temperature range	15 to 32.5° C
Recommended humidity operating range	30 to 70% RH
ENERGY STAR® qualified	No
What's included	
Warranty	1 Year Limited Warranty (Return to HP/Dealer - Standard Bench Repair)
What's in the box	Printer; power cord; full-capacity print cartridge; software and documentation on CD-ROM; Getting Started Guide; support flyer; Warranty Guide (where applicable)

ADVANTAGE
LASER PRODUCTS, INC.

www.advlaser.com

800-722-2804 • 404-351-2700

www.advlaser.com